


# HOW TO USE THE CIRCULAR SEWING ATTACHMENT

## ★Preparation

### ①Preparing the sewing machine


Upper thread tension : Auto or standard  
 Needle : #11 or #11 blue tip  
 Pressure dial : 2

### ②Release the hook cover plate.




\* Slide the hook cover plate release button to the right, and take off the hook cover plate.

### ③Slide the center plate to the left.




\* Push the lock lever in the direction of the arrow, and slide the center plate left as far as it will go.

### ④Fasten the attachment.




\* Match the attachment to left side of the attachment holder hole and press it down where the arrow shows.

### ⑤Set the radius of the circular you want to sew.



\* Match the set mark to the diameter of your circle by sliding the center plate.




\* The upper scale is centimeters, the lower, inches.

\* The scale corresponds to a radius of the circle sewn using straight stitch set in middle needle position.


\* Secure the center plate, pushing the lock lever in the direction of the arrow.

### ⑥Make a design combining circles.



\* Make a design on paper combining many circles with a compass as shown.


### ⑦Transcribe the center of circle on the cloth.



\* Transcribe the center of each circle in the design to the cloth using French chalk paper.

\* When sewing on soft cloth, attach an iron-on backing to the back of your cloth before sewing.


### ⑧Set the cloth.



\* Remove the center cap and pierce the needle in the center of the circle marked on the cloth.

## ★How to sew

### ⑨Sew the circle.




\* Replace the center cap on the needle.

\* Sew, guiding the cloth circularly around the center cap.

\* Sew your remaining circles following the same steps as above.

### ⑩Remove the attachment.



\* Push the lock lever in the direction of the arrow, and slide the center plate leftmost.

\* Slide the hook cover plate release button to the right, and remove the attachment pushing downward as the arrow shows.

